

Gasoilne

Oilload/> Open Specification Gasoline
Loading> May 10,2026 | Only for Export

Parameter	A91	A92	A95	A97	Unit	Reference Standard
RON (Research Octane Number)	91.0 min	92.0 min	95.0 min	97.0 min	-	ASTM D2699
MON (Motor Octane Number)	82.0 min	83.0 min	85.0 min	87.0 min	-	ASTM D2700
AKI	86.5	87.5	90.0	92.0	-	-
Density @ 15°C	0.720 – 0.760	0.725 – 0.765	0.730 – 0.770	0.735 – 0.775	g/cm ³	ASTM D4052
Total Sulfur	Max 50	Max 50	Max 50	Max 50	ppm	ASTM D4294
Benzene	Max 0.8	Max 0.7	Max 0.5	Max 0.4	% Vol	ASTM D6277
Aromatics	Max 35	Max 35	Max 35	Max 32	% Vol	ASTM D6277
Olefins	Max 10	Max 8	Max 5	Max 3	% Vol	ASTM D6277
Oxygen Content	Max 2.7	Max 2.7	Max 2.7	Max 2.7	% Mass	ASTM D5845
MTBE	5 – 12	6 – 13	8 – 15	10 – 18	% Vol	ASTM D5845
Ethanol	0 – 2.5	0 – 2.5	0 – 2.0	0 – 2.0	% Vol	-
Initial Boiling Point (IBP)	35 – 45	35 – 45	36 – 46	37 – 47	°C	ASTM D86
T50	95 – 110	95 – 110	98 – 112	100 – 115	°C	ASTM D86
T90	160 – 175	160 – 175	162 – 178	165 – 180	°C	ASTM D86
Final Boiling Point (FBP)	Max 195	Max 195	Max 195	Max 195	°C	ASTM D86
Reid Vapor Pressure (RVP)	45 – 65	45 – 65	45 – 60	45 – 60	kPa	ASTM D6378
Appearance	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright	-	ASTM D4176

Note: All grades are customizable according to buyer requirements (higher Octane, specific additive packages, etc.). Delivery: FCA Erbil / Sulaymaniyah or border delivery.